

SANY®



الخريف التجارية
Alkhorayef Commercial



-  Fuel Efficiency
-  High Reliability
-  Driving Comfort

SL-525

SANY Diesel Truck

✉ info@alkhorayef.com ☎ 920002985 🌐 www.alkhorayefcommercial.com

✕ 📺 📱 📷 Alkhorayefcommercial | ✕ 📷 sanytrucksksa 📱 Sany Trucks KSA

SL-525

FUEL EFFICIENCY

Powered by the German Deutz D13 engine, the truck achieves a 1% reduction in fuel consumption. Boasting 525 horsepower, it outperforms competitors and is well suited for expressway logistics scenarios.

HIGH RELIABILITY

All components meet C5 corrosion/dust/water resistance standards, Million-kilometer validated reliability, it guarantees an extended service life.

DRIVING COMFORT

Featuring a spacious flat-floor cab, stylish exterior and modern interior, the vehicle offers outstanding quietness, superior driving comfort and high reliability.

PRODUCT TECHNICAL SPECIFICATION

Host Code			KQY100001103
Basic Parameters	Drive Type		4×2
	Driver's Seat Location (Left/Right)		Left Hand Drive
	Length × Width × Height (unladen) (mm)		6595×2590×3935
	Emission		Euro V
	Wheel Base (mm)		4000
	Front Overhang (mm) / Rear Overhang (mm)		1515/1080
	The Fifth-Wheel		50#
	Height of the Fifth-wheel from Ground Without Load (mm)		1270
	Front Bumper Ground Clearance (mm)		530
	Minimum Ground Clearance (mm)		240
	Front Turning Radius (mm)		2200
	Rear Turning Radius (mm)		1730
	Curb Weight (kg)		7500
	Gross Combination Weight (kg)		45000
Frame Parameter	Section Height×Section Width×Frame Thickness (mm)		300×(940-850)×(8+5), Partial Double-Layer Strengthened Frame
Engine	Type		D13C3-525E2
	Rated Power (Hp) / (rpm)		525/1900
	Max Torque (Nm) / (rpm)		2550/1000-1400
Transmission	Type (AMT/MT)		F12JZ22
	Number of Gears		Forward Gear 12, Reverse Gear 2
	Ratio		1th Gear Ratio 15.70, 12th Gear Ratio 1
Brake	Type		ABS
Cab	Configuration Description		High-roof Flat Floor, Air Deflector, DAB+Video, 7-inch Instrument Cluster, Upper and Lower Berths, Driver's Air Suspension Seat, Warning Lights, Automatic Adjustable Rear Mirror, Electric Air Conditioning, Electric Tilt Cab, Comfortable Steering Wheel, Electric Window
Axle	Front	Load Capacity (t)	7
	Middle/ Rear	Load Capacity (t)	13
		Ratios	2.846
Tyres	Model		Front: 385/65R22.5, Rear: 315/80R22.5
Suspension	Front /Rear		Front 3 Leaf Spring/Rear 3+3 Leaf Spring
Battery	Voltage (V)		24 (12×2)
	Battery Capacity (Ah)		165
Fuel	Type		Aluminum Fuel Tank, with Lockable Cap
	Capacity		600L (800L Optional)
Trailer electrical			7pin
Trailer power supply			24V
Alternate Configuration			Air Deflector and PTO Optional; Transmission & Axle Ratio: Standard Direct Drive +2.846, Overdrive +3.7 Optional; Fifth-wheel Type: Standard Stamping Process, Casting Process Optional.