

SANY[®]



الخريف التجارية
Alkhorayef Commercial



-  Long Durability
-  High Load-bearing Capacity
-  Strong Power

SL-485

SANY Diesel Truck

✉ info@alkhorayef.com ☎ 920002985 🌐 www.alkhorayefcommercial.com



Alkhorayefcommercial |



sanytrucksksa Sany Trucks KSA

SL-485

LONG DURABILITY

Adopt heavy-duty high-strength chassis, which is stronger and longer-lasting than the competitor's chassis.

HIGH LOAD-BEARING CAPACITY

8+ partially reinforced high-strength frame, front 3 and rear 3+4 variable-section leaf spring suspension.

STRONG POWER

Deutz D13C5-485, super 485 horsepower, has obvious power advantages over competitors.

PRODUCT TECHNICAL SPECIFICATION

Host Code			KQY100001076	
	Drive Type		4×2	
Basic Parameters	Length×Width×Height(unladen) (mm)		6465×2550×3935	
	Emission		Euro V	
	Wheel Base (mm)		4000	
	Front Overhang/Rear Overhang (mm)		1515/950	
	The Fifth-Wheel		50#	
	Height of the Fifth-Wheel from Ground Without Load (mm)		1270	
	Front Bumper Ground Clearance (mm)		530	
	Minimum Ground Clearance(mm)		240	
	Front Turning Radius(mm)		2200	
	Rear Turning Radius(mm)		1730	
	Curb Weight (kg)		7500	
	Gross Combination Weight (kg)		45000	
	Frame Parameter	Section Height×Section Width×Frame Thickness(mm)		300×（940-850）×8, Partial Double-Layer Strengthened Frame
Engine	Type		D13C5-485E2	
	Rated Power (hp) / (rpm)		485/1900	
	Max Torque (N·m) / (rpm)		2350/1000-1400	
Transmission	Type		F12JZ24A+QHG50C（AMT）	
	Number of Gears		Forward Gear 12, Reverse Gear 2	
	Ratios		1th Gear Ratio 12.26, 12th Gear Ratio 0.78	
Brake System	Type		ABS+ASR	
Cab	Configuration Description		High-roof Flat Floor, Left-hand Drive, Wind Deflector, 12.1-inch Large Screen, 7-inch Instrument Cluster, Upper and Lower Berths, Driver's Air Suspension Seat, Warning Lights, Automatic Adjustable Rear Mirror With Electric Heating Function, Electric air Conditioning, Electric Tilt Cab, Multi-function Steering Wheel, Electric Window Lifts.	
Axle	Front	Load Capacity (t)	7.5	
	Middle/Rear	Load Capacity (t)	13	
		Ratio	3.866	
Tyres	Model		Front: 385/65R22.5, Rear: 315/80R22.5	
Suspension	Front /Rear		Front 3 Leaf Spring/Rear 3+4 Leaf Spring	
Battery	Voltage (V)		24(12×2)	
	Battery Capacity (Ah)		180	
Fuel	Type		Aluminum Fuel Tank, With Lockable Cap	
	Capacity		500L+300L	
Trailer Electrical Interface			7pin	
Trailer Power Supply			24V	
Addition			Optional 360°-Degree Surround View System, ADR, 4.111 / 3.7 Rear Axle Ratios, Side Underrun Protection	